

**DP****1040**

## INDUSTRIAL GASKET TAPE

**A gasket tape designed to seal metal to metal joints encountered in many industrial fabrication applications. DP 1040 is particularly efficient for leak proofing metal joints found in HVAC systems.**

### Recommended Uses:

1. Provides an efficient airtight and watertight flexible seal for metal to metal joints.
2. Used for leak proofing metal joints.
3. For sealing and preventing the entry of dust, air and moisture through details found in HVAC systems.
4. Used where a moldable gasket seal is required.

### Directions For Use:

**Surface Preparation:** Surfaces should be clean, dry and free of dirt, oil and any foreign matter.

**Application:** Position DP 1040 on required seal area with backing paper on top. Using a smooth even hand motion, press the tape to the surface to make contact without distorting the tape sealant. Avoid overlapping the tape by butt joining tapes at transition points. Remove backing paper prior to mating adjoining surface.

**Limited Product Warranty:** Design Polymerics is not liable for consequential incidental or special damages. There are no statutory or implied warranties including the warranties of fitness for a particular purpose and merchantability. There are no warranties other than set forth below and Design Polymerics neither assumes nor authorizes any person to assume any liability or other obligation in connection with the DP 1040. It shall be the sole responsibility of the user to determine the suitability of DP 1040 for each intended use and the user shall assume all risks and liability in connection with the use, or inability to use, the product or material. Design Polymerics does not guarantee the results from the use of DP 1040 because of the extreme differences in surface texture, the porosity of available materials and the possibility of externally caused damage. DP 1040 is warranted to be free from any and all defects in material and workmanship only at the time of shipment from our plant. Design Polymerics will replace or issue credit for the original purchase price.

### Features and Benefits:

- UL Classified
- Excellent Workability
- Adhesion to Most Non-Porous Surfaces
- Withstands Joint Movement Without Cracking
- Excellent Water and U.V. Resistance
- Non-Drying
- Non-Skinning
- Non-Oxidizing

### Technical Data:

**Color:** Light Grey

**Odor:** Odorless

**Solids Content:** 100%

**Service Temperature:** -25° - 180°F

**Application Temperature:** 0°F - 120 °F

**Shelf Life:** 18 months

**Elongation:** 200% min.

**U.L. -723, ASTM E-84**

**Flame Spread:** 5

**Smoke Density:** 5

**NFPA:** Class A

**Uniform Business Code:** Class 1

**Packaging:** 5/8" x 3/16" x 25' (20 rolls per ctn.)



11609 Martens River Circle  
Fountain Valley, CA 92708  
Toll Free 800.641.0808  
Phone 714.432.0600  
Fax 714.432.0660

